

FIAT

4 |
 3 |
 4



UPHOLSTERY



PRESTIGE

Imitation leather and fabric
Standard



PRESTIGE BROWN

Imitation leather
Optional

PACK

KEA P

PACK MATIC 140 HP/180 CV

140 HP / 180 HP Engine, Automatic transmission, 16" glossy black alloy wheels, light suspensions

•

PACK EXTRA TECH

Full digital cluster, automatic climate control, wireless charger, full LED headlights

•

PACK PREMIUM

2 DIN Apple Car Play / Android Auto radio, dual purpose rear view camera, 200 W solar panel + MPPT Controller

•

PACK VISIO

2 DIN Apple Car Play / Android Auto radio, dual purpose rear view camera

-

PACK ARCTIC

Truma Combi 6E, "Duo Control" gas regulator, heated windscreen (A-class), external covers, internal dashboard cover

-

PACK EXTRA WARM

Truma Combi 6E, "Duo Control" gas regulator, heated windscreen (A-class), external covers, internal dashboard cover, heated floor, insulated step

•

PACK ENERGY

Compressor fridge, two 100 Ah lithium batteries

•

PACK OUTDOOR

External gas connector, external TV / 12 V / 220 V connector, external shower

•

PACK MEDIA

Router Wi-fi, Smart TV

• TV 24"

KEA P 86	WEIGHT	ELEVATING BED	LOW-PROFILE
CHASSIS			
Mechanical unit	--	Fiat Ducato	Fiat Ducato
Engine, Power	--	2,2 MJ 140 HP	2,2 MJ 140 HP
Maximum technically permissible weight (kg)	--	3500	3500
Weight unladen in running conditions (kg)	--	3030	3030
Pay Load (Kg)	--	470	470
Wheelbase (mm)	--	4035	4035
Maximum towable weight (kg)	--	2000	2000
Wheels dimensions	--	16"	16"
Fuel tank (L)	--	90	90
DIMENSIONS, PLACES AND MATERIALS			
Locker (useful opening, cm)	--	117 x 87(72) - 117 x 87(72)	117 x 87(72) - 117 x 87(72)
Max. internal garage height (cm)	--	119,5	119,5
Floor/walls/roof thickness (cm)	--	5,4 / 3 / 3	5,4 / 3 / 3
Floor/walls/roof material (mm)	--	MTS / VTR / VTR	MTS / VTR / VTR
Fiberglass roof, hail-proof	--	S	S
BERTHS			
Rear Bed (cm)	--	205 x 80 - 208,5 x 80	205 x 80 - 208,5 x 80
Elevating Bed (cm)	--	190 x 128(107)	-
Additional seat rear bed	--	S	S
Auxiliary bed in dinette	--	O	S
Dimensions Auxiliary bed in Dinette (cm)	1	216 x 98,6(80)	216 x 98,6(80)
SKYLIGHTS			
Panoramic roof (mm)	--	S (1000 x 800)	S (1000 x 800)
Rear skylight (mm)	--	S (700 x 500)	S (700 x 500)
Central skylight (mm)	--	S (400 x 400)	S (400 x 400)
Dinette skylight	--	-	S (960x655)
Skylight toilette/shower (mm)	--	400 x 400 / 280 X 280	400 x 400 / 280 X 280
Double-glazed windows with blind / mosquito net	--	S	S
INSTALLATIONS			
Burners / Gas oven	--/14	2 / O	2 / O
Tank capacity : clear water / wastewater (L*)	--	(20) 120 / 95	(20) 120 / 95
Automatic trivalent fridge (220V, 12V, gas) (L)	--	145	145
Standard heating system	--	Combi gas 6KW	Combi gas 6KW
Space for 2 gas bottles (tot. Max 15 Kg)	--	S	S
Shower tray with double drain	--	S	S
Integrated and isolated entry step	--	S / O	S / O
Heated garage locker	--	S	S
Storage compartment floor hatch	--	S	S
CHASSIS EQUIPMENTS			
Manual air conditioning	--	S	S
Driver and Passenger airbag	--	S	S
Cruise Control with speed limiter	--	S	S
ABS / ESC / Traction+	--	S / S / S	S / S / S
Swivelling driver' and passenger's seat	--	S	S
Cab seat covers	--	S	S
Painted front bumper	--	S	S
Fog lights	--	S	S
Electric handbrake	--	S	S
TPMS	--	S	S
Techno dashboard	--	S	S
Leather steering wheel and gear box	--	S	S
BODY EQUIPMENTS			
Pleated cab blind	--	S	S
Beds with staves	--	S	S
Internal LED lightening	--	S	S
Premium XL Entrance door with two central locking points	--	S	S
Flyscreen for sliding door	--	S	S
Strip opening with locker	--	S	S
External LED light	--	S	S
TECHNOLOGY EQUIPMENTS			
Tekni-Box	--	S	S
Open door sensor	--	S	S
Double battery system	--	S	S

Measures in cm except where otherwise indicated
S= standard O=optional - = not available
VTR=Fiberglass MTS=multilayer

*To increase the vehicle payload, when travelling it is possible to reduce the fresh water tank capacity to approx. 20 lt.

The mass in running order includes the weight of the empty base vehicle, of the driver (75 kg), 100% of the fuel (60-l tank), fresh water (tank filled with 20 l while travelling), and aluminium gas cylinders (max.15 kg) filled to 90% of their capacity, and tolerance specified in the type-approval (+/- 5%) (2007/46/EC). Anything not included in the standard version of the vehicle, both living unit and chassis, results in an increase in weight in running order with resulting decreased payload up to the possible reduction of approved seats in the case of the total weight for the available payload value. The available payloads result from the difference between maximum permissible mass and running order mass and have a tolerance of 5%. During the purchase phase it is necessary to check the weight of the options to be installed on the vehicle.

