



SERIES 300 GLAMYS 322



HOMOLOGATED SEATS	7
SLEEPS	7
SEATS AT THE TABLE	6



FORD PACK

SERIES 300 FORD PACK

FORD MATIC PACK – Series 300 Ford Pack required

DESIGN PACK – Series 300 Ford Pack and Matic Pack required

EXTRA ASSISTANCE PACK – Series 300 Ford Pack and Matic Pack required

FIAT PACK

SERIES 300 FIAT PACK

FIAT MATIC PACK - Series 300 Fiat Pack required

FIAT EXTRA TECH PACK - Series 300 Fiat Pack required

EXTRA SAFETY PACK - Series 300 Fiat Pack and Extra Tech Pack required

FORD & FIAT PACK

ENJOY OUTDOOR PACK

EXTRA WARM / EXTRA WARM DIESEL PACK

24" DIGITAL / SATELLITE TV PACK

24" TV WI-FI PACK

See final table for pack details

Chassis	FIAT	Ford
Engine, Power	2,2 MJ 140 HP	2.0 TDI 130 HP
Maximum technically permissible weight (kg)	3500	3500
Weight unladen in running conditions (kg)	2850	2880
Pay Load (kg)	650	620
Wheelbase (mm)	3800	3750
Maximum towable weight (kg)	2000	2000
Wheels dimensions	15"	16"
Automatic air conditioning	O	S
Driver and Passenger airbag	S	S
Cruise Control with Intelligent Speed Assist	O	S
ABS / ESC / ESP /TRACTION +	S/S/-S	S/-S/-
Driver and passenger swivelling seats	S	S
4 season tyres	S	-
Steering wheels control	S	S
9" touch screen radio / 12" touch display with SYNC 4 infotainment and 5G modem	S/-	-/S
Dimensions and places		
External length (mm) / External width (mm)	6990 / 2350	
External height(cm) / Internal height (cm)	320 / 208	
Auxiliary bed in dinette	S	
Rear Bed (cm)	212x87(74) - 212x83(70)	
Dimensions Auxiliary bed in Dinette (cm)	180x121 - 140x64	
Overcab bed (cm)	209x160	
Locker (useful opening, cm)	125x70 - 125x60	
Max. internal garage height (cm)	138	
Floor / walls / roof thickness (cm)	5,4 / 3 / 3	
Floor / walls / roof material	MTS / VTR / VTR	
Fiberglass roof, hail-proof	S	
Installations		
Burners	2	
Tank capacity : clear water / wastewater (l)	20(100) / 100	20(100)/120
Automatic trivalent fridge (220V, 12V, gas) (l)	137	
Standard heating system	Combi Gas 4 kW	
Space for 2 gas bottles (tot. Max 15 kg)	S	
Integrated entry step	S	
Heated garage locker	S	
Skylight		
Rear skylight (mm)	S (400x400)	
Dinette skylight (mm)	S (400X400) / O (700X500)	
Toilette skylight (mm)	S (280X280)	
Double-glazed windows with blind / mosquito net	S	
Equipments		
Thermal blind	S	
Beds with staves	S	
CP Plus control panel	S	
Internal LED lightening	S	
Exteriors		
Fog lights	O	S
Rear-view camera	S	
Flyscreen for entrance door	S	
XL Entrance door	S	
External LED light	S	

* Window in the bathroom without blind and mosquito net

S= standard O=optional VTR= Fibreglas MTS= multi-layered plywood
The mass in running order includes the weight of the empty base vehicle, of the driver (75 kg), 100% of the fuel, fresh water (tank filled with 20 l while travelling), and aluminium gas cylinders (max.15 kg) filled to 90% of their capacity, and tolerance specified in the type-approval (+/- 5%) (2007/46/EC). Anything not included in the standard version of the vehicle, both living unit and chassis, results in an increase in weight in running order with resulting decreased payload up to the possible reduction of approved seats in the case of the total weight for the available payload value. The available payloads result from the difference between maximum permissible mass and running order mass and have a tolerance of 5%. During the purchase phase it is necessary to check the weight of the options to be installed on the vehicle.